




QQ-2702A 二节精密静音滚珠滑轨 2-Fold Precise & silent ball bearing slide



Thickness	
NO.	材料厚度
①	1.2mm
②	1.2mm



Slide Length mm	Slide Travel mm	A mm	Weight Capacity lbs/kg	Weight g/set	Carton set
246	172		77/35	325	30
278	204	32	72/33	367	30
310	212	64	66/30	409	30
342	244	96	61/28	452	30
374	252	128	55/25	494	30
406	284	160	50/23	536	30
438	316	192	44/20	578	30
470	324	224	38/17	620	30
502	356	256	33/15	663	30

■ **建议用途:**轻承载的活动柜, 柜台抽屉, 一般家具或任何需要20公斤或以下承载, 要求3/4展的用途。

■ **产品特点:**不可分离。

■ **表面处理:**蓝白锌, 黑色电泳, 三价铬环保镀锌。

■ **承载重量:**44磅/20kgs (18" 滑轨)

■ **材料选择:**冷轧钢, 不锈钢。

■ **Suggested Applications:**light-duty movable cabinet, desk drawer, ordinary furniture or any applications requiring 20kgs load or less and requiring 3/4 extension

■ **Features:**inseparable



■ **Finish:**blue-white zinc plating, black electrophoresis, environmental zinc plating with trivalent chromium

■ **Weight Capacity:**44lbs/20kgs(for 18")

■ **Material:**cold-rolled steel, stainless steel



QQ-2703A 二节精密静音烤炉滚珠滑轨 2-Fold Precise & silent ball bearing slide for oven



Thickness	
NO.	材料厚度
①	1.2mm
②	1.2mm

■ **建议用途:**烤炉。

■ **承载重量:**44磅/20kgs (16" 滑轨)

■ **材料选择:**冷轧钢, 不锈钢。


■ **Suggested Applications:**oven

■ **Weight Capacity:**44lbs/20kgs(for 16")

■ **Material:**cold-rolled steel, stainless steel



QQ-2704A 三节精密静音叠加型滚珠滑轨 3-Fold Precise & silent overlapping ball bearing slide



Slide Length mm	Slide Travel mm	Weight Capacity lbs/kg	Weight g/set	Carton set
246	250	132/60	650	20
278	282	128/58	735	20
310	314	118/54	820	20
342	346	110/50	900	20
374	378	105/48	988	20
406	410	96/44	1070	15
438	442	88/40	1156	15
470	472	84/38	1240	15
502	506	77/35	1325	15
534	538	66/30	1400	15



Thickness NO.	材料厚度
①	1.2mm
②	1.2mm

- **建议用途:**中承载的活动柜, 柜台抽屉, 一般家具或任何需要45公斤或以下承载, 要求全展的用途。
- **产品特点:**完全拉出。
- **表面处理:**蓝白锌, 黑色电泳, 三价铬环保镀锌。
- **承载重量:**88磅/40kgs (18" 滑轨)
- **材料选择:**冷轧钢, 不锈钢。

- **Suggested Applications:**medium-duty movable cabinet, desk drawer, ordinary furniture or any applications requiring 45kgs load or less and requiring full extension
- **Features:**full extension
- **Finish:**blue-white zinc plating, black electrophoresis, environmental zinc plating with trivalent chromium
- **Weight Capacity:**88lbs/40kgs(for 18")
- **Material:**cold-rolled steel, stainless steel



QQ-2704B 三节精密静音叠加型滚珠滑轨 3-Fold Precise & silent overlapping ball bearing slide




Thickness NO.	材料厚度
①	1.2mm
②	1.2mm

- **建议用途:**中承载的烤炉, 消毒柜, 橱柜等。适用于潮湿, 高温腐蚀性的环境使用, 永不生锈, 或任何需要45公斤或以下承载, 要求全展的用途。
- **产品特点:**简便的挂插式安装, 快速分离机构, 避震珠吸收冲撞, 防止抽屉弹出机构。
- **承载重量:**88磅/40kgs (16" 滑轨)
- **材料选择:**sus304不锈钢

- **Suggested Applications:**medium-duty oven, disinfection cabinet, kitchen cabinet, etc., suitable for damp, hot, corrosive environment or any applications requiring 45kgs load or less and requiring full extension
- **Features:**bayonet mounting-easy and quick installation and removal, rapid separation of institutions, vibration prevention ball strip for absorbing impulsive force, mechanism to prevent the drawer pops out.
- **Weight Capacity:**88lbs/40kgs(for 16")
- **Material:**SUS304 stainless steel



QQ-2704A 三节精密静音叠加型滚珠滑轨 3-Fold Precise & silent overlapping ball bearing slide



Slide Length mm	Slide Travel mm	Weight Capacity lbs/kg	Weight g/set	Carton set
246	250	132/60	650	20
278	282	128/58	735	20
310	314	118/54	820	20
342	346	110/50	900	20
374	378	105/48	988	20
406	410	96/44	1070	15
438	442	88/40	1156	15
470	472	84/38	1240	15
502	506	77/35	1325	15
534	538	66/30	1400	15


Thickness NO.	材料厚度
①	1.2mm
②	1.2mm

- **建议用途:**中承载的活动柜, 柜台抽屉, 一般家具或任何需要45公斤或以下承载, 要求全展的用途。
- **产品特点:**完全拉出。
- **表面处理:**蓝白锌, 黑色电泳, 三价铬环保镀白锌。
- **承载重量:**88磅/40kgs (18" 滑轨)
- **材料选择:**冷轧钢, 不锈钢。

- **Suggested Applications:**medium-duty movable cabinet, desk drawer, ordinary furniture or any applications requiring 45kgs load or less and requiring full extension
- **Features:**full extension
- **Finish:**blue-white zinc plating, black electrophoresis, environmental zinc plating with trivalent chromium
- **Weight Capacity:**88lbs/40kgs(for 18")
- **Material:**cold-rolled steel, stainless steel



QQ-2704B 三节精密静音叠加型滚珠滑轨 3-Fold Precise & silent overlapping ball bearing slide




Thickness NO.	材料厚度
①	1.2mm
②	1.2mm

- **建议用途:**中承载的烤炉, 消毒柜, 橱柜等。适用于潮湿, 高温腐蚀性的环境使用, 永不生锈, 或任何需要45公斤或以下承载, 要求全展的用途。
- **产品特点:**简便的挂插式安装, 快速分离机构, 避震珠吸收冲撞, 防止抽屉弹出机构。
- **承载重量:**88磅/40kgs (16" 滑轨)
- **材料选择:**sus304不锈钢

- **Suggested Applications:**medium-duty oven, disinfection cabinet, kitchen cabinet, etc., suitable for damp, hot, corrosive environment or any applications requiring 45kgs load or less and requiring full extension
- **Features:**bayonet mounting-easy and quick installation and removal, rapid separation of institutions, vibration prevention ball strip for absorbing impulsive force, mechanism to prevent the drawer pops out.
- **Weight Capacity:**88lbs/40kgs(for 16")
- **Material:**SUS304 stainless steel



QQ-2705A 二节精密静音烤炉滚珠滑轨
2-Fold Precise & silent ball bearing slide for oven



- 建议用途:烤炉。
- 承载重量:44磅/(20kgs)/组
- 材料选择:304不锈钢, 430不锈钢。
- Suggested Applications:oven
- Weight Capacity:44lbs/20kgs
- Material:304 stainless steel, 430stainless steel.




伸展 Extension


75%伸展: 是指抽屉打开的长度大概为导轨长度的75%
75% extension: extension length 75% of the slide length





100%伸展: 是指抽屉打开的长度为滑轨长度的100%
100% extension: extension length 100% of the slide length



超100%伸展: 是指抽屉打开的长度超过滑轨的长度
over extension: extension length more than 100% of the slide length



双向拉伸滑轨: 是指从前后两边都可以打开抽屉
bidirectional extension: can be opened from both sides



SL=

Slide length

Longitud de la guida

Lunghezza della guida

TR=

Travel

Recorrido

Corsa



滑轨安装高度 Slide height

滑轨安装高度是指安装侧面滑轨所需要的距离。为了更好的滑动，允许在正常的滑轨厚度上加上0.2mm-0.5mm的距离。比如说：12.7mm厚度的滑轨，安装高度允许在12.9mm-13.2mm之间。

slide height: +0.2mm-+0.5mm of the slide thickness is allowed. For example: slide thickness is 12.7mm, the slide height should be between 12.9mm and 13.2mm.

材料 Material

滑轨：冷轧钢、镀锌板、不锈钢

Slide: cold-rolled steel, galvanized steel, stainless steel

保持架：冷轧镀锌板、不锈钢、塑料

Cage: cold-rolled galvanized steel, stainless steel, plastic

钢球：碳钢、不锈钢

Ball: carbon steel, stainless steel

滑轨的润滑与维护

奇强滑轨采用高低温油脂，一般情况下，标准的工作温度为-20℃-+120℃。但在一些特殊的环境中，滑轨的工作温度可高达300℃，这就需要添加特殊的耐高温润滑油。

奇强滑轨在生产的时候已经进行很好的润滑，都是免维护的。但是考虑到滑轨的工作环境的不同，应时常对其进行检查，及时清除污物，重新润滑滑轨。这样可以降低滑轨的摩擦力，减少零部件磨损，延长滑轨寿命。

With the high temperature and low temperature lubricants, the standard operation temperature of "Qiqiang" slide is between -20℃ and +120℃. But if necessary, the temperature can be higher up to 300℃, and special high temperature lubricants are necessary.

"Qiqiang" slides are fully installed and greased before delivery, they are virtually maintenance free. Depending on the different operating environment, they should be checked from time to time, dirt should be removed, and slide should be regreased, so as to protect the assembly parts and prolong the slide's life.



滑轨寿命测试机 Slide Life Test Instrument



自动装配线 automated assembly lines



型材车间 Profile Converting Shop



模具车间 Mould Workshop



盐雾测试机 Hydrochloric Test Instrument



高清数据测绘仪 HD Computer controlled mapper